

Plumbing Instructions

Be sure electrical wiring to disposer is disconnected from power.
Be sure circuit breakers are turned off before installing. And be sure to wear safety glasses.



Remove mounting hardware



Put lip into mounting seal*



Attach clamp



Insert drain lip into seal



Attach clamp

Once disposal is attached, follow the disposal manufacturer's instructions and safety precautions for attaching plumbing, electrical power, and operation.

Drain fitting is ready for drain plumbing to be attached.

Plug sink and fill with water to test for leaks.



Helpful tips for an easy install:

Liquid dish soap can be used as a seal lubricant prior to the lip insertion. (Never use oil or grease)

Push or pull the drain or disposer to stretch the rubber seal to stretch it, then drop the back end in.

The clamp is designed to attach if seal is seated properly. Gently wiggle disposer and drain to seat the seal.

Start one side of clamp and make sure it is seated properly (Notice how close the clamp is to the seal), then close the other side.

Make sure no paint or sound pads are touching the clamp or seal. If they do scrape the paint and cut that part of pad away.

*For added leverage, place the base of the disposal in the palm of your hand and put that elbow on the floor of the cabinet. The other hand guides the throat and lip into the rubber mounting seal.



There are 4 disposer brackets on the US market.

3 of those disposers have the same lip when their brackets are removed.

The other disposer mount uses an adapter.

The adapter's lip slips into the mounting seal and is attached with a clamp as above.

If adapter is needed, contact us and we will ship at no charge

PermaClean Drain System is not designed to fit Batch Feed Disposals. But there is one; the Waste King 9000 series batch feed disposer.

If any questions, call tech support at 1-513-277-0491 or visit our web site at www.LenovaSinks.com

